

H-TK.R

油位观察窗

材料

- 钢,电镀镍表面处理.
- 液位分割器-不锈钢AISI304(因尺寸约束,小规格亦或不提供).
- 观察窗-钙钠玻璃,由高温烧制工艺将玻璃与本体融合一起.

最高连续工作温度

- $-40^{\circ}\text{C} \sim 280^{\circ}\text{C}$.

特殊定制方案

- 可按需提供不同的表面处理方式:
- 钝化的表面处理.
- 环保电镀锌的表面处理.
- 镀铬的表面处理.
- 达克罗的表面处理.
- 锌镍合金的表面处理.

技术特性

- H-TK油位观察窗因特殊工艺制作,使得该部件可在高温差以及高压差的环境中使用,通常使用于冷媒行业,高压容器,化工以及医疗设备行业.

Oil level window

Material

- Steel, nickel plated surface treatment.
- Reflector – stainless steel AISI304.
- Window – High temperature sintering glass.

Maximum continuous working temperature


- $-40^{\circ}\text{C} \sim 280^{\circ}\text{C}$.

Accessories on request

- Different surface treatments can be provided on demand.
- Passivation of surface treatment.
- Zinc plated nano-passivated.
- Chromium plated surface treatment.
- Dacromet electroplated.
- Zn-ni alloy electroplating.

Technical information

- H-TK oil level window is fabricated by special technology, which makes it suitable for use in high temperature and high pressure environment. It is usually used in refrigerant, high pressure vessel, chemical and medical equipment industries.



Pr-Nr.	G	L	L1	d	HEX	Max(Mpa)
TK.R-12R	NPT 1/2"	20	14	14	24	5
TK.R-16R	NPT 3/4"	24	17	18	27	5
TK.R-22R	NPT 1"	27	19	25	36	5
TK.R-28R	NPT 1 1/4"	31	21	30	45	5
TK.R-33R	NPT 1 1/2"	31	21	36.5	50	5
TK.R-43R	NPT 2"	33	23	44.5	64	5